

Interflon Fin Super Dry Lube

Version number: 1.7

Revision: 2020-04-02:

SECTION 1: Identification

1.1 Product identifier

Trade name **Interflon Fin Super Dry Lube**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Applications lubricant

1.3 Details of the supplier of the safety data sheet

Interflon BV
Belder 47
4704 RK Roosendaal
Netherlands

Telephone: +31 (0)165 553911
e-mail: Service@interflon.com
Website: www.interflon.com

e-mail (competent person) Service@interflon.com (Service lab)

1.4 Emergency telephone number

Official advisory body

Poison center

Poison center					
Country	Name	Postal code/ city	Telephone	Telefax	Opening hours
United States	Poison control - National Capitol Poison Center		1-800-222-1222		Mon - Fri 12:00 AM - 11:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07



Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

- Hazard statements

H227 Combustible liquid.
H319 Causes serious eye irritation.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P280 Wear protective gloves/eye protection/face protection.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

This material is combustible, but will not ignite readily.

Hazards not otherwise classified

Repeated exposure may cause skin dryness or cracking.
Contains . May produce an allergic reaction.
Toxic to aquatic life (GHS category 2: aquatic toxicity - acute).

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Product description

Mixture of mineral and vegetable oils, additives and Micpol®

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	CAS No 64742-47-8	50 - < 75	Asp. Tox. 1 / H304 Flam. Liq. 4 / H227
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	CAS No 110-25-8	0 - < 2.5	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Dam. 1 / H318
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylenedi-, ethoxylated(NLP)	CAS No 1290049-56-7	0 - < 2.5	Acute Tox. 3 / H301 Skin Corr. 1B / H314 Eye Dam. 1 / H318 STOT RE 1 / H372

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

SECTION 4: First-aid measures**4.1 Description of first- aid measures**

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures**5.1 Extinguishing media**

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Conditions of storage

Store in accordance with local/regional/national/international regulations. Keep container tightly closed and in a well-ventilated place.

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

no data available

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	DNEL	0.8 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylenedi-, ethoxylated(NLP)	1290049-56-7	DNEL	0.12 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylenedi-, ethoxylated(NLP)	1290049-56-7	DNEL	0.017 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	PNEC	0.43 µg/l	aquatic organisms	freshwater	short-term (single instance)
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	PNEC	0.043 µg/l	aquatic organisms	marine water	short-term (single instance)
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	PNEC	1 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	PNEC	0.007 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	PNEC	0.001 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	PNEC	1.71 mg/kg	terrestrial organisms	soil	short-term (single instance)

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylenedi-, ethoxylated(NLP)	1290049-56-7	PNEC	2 µg/l	aquatic organisms	freshwater	short-term (single instance)
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylenedi-, ethoxylated(NLP)	1290049-56-7	PNEC	0.2 µg/l	aquatic organisms	marine water	short-term (single instance)
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylenedi-, ethoxylated(NLP)	1290049-56-7	PNEC	1.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylenedi-, ethoxylated(NLP)	1290049-56-7	PNEC	7.5 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylenedi-, ethoxylated(NLP)	1290049-56-7	PNEC	0.75 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylenedi-, ethoxylated(NLP)	1290049-56-7	PNEC	5 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

General safety precautions

Use only in well-ventilated areas.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.
Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Physical state	liquid
Color	yellowish brown
Odor	Like Oil

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	201.7 °C at 99,796 Pa
Flash point	83 °C at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	1 vol%
- Upper explosion limit (UEL)	8 vol%

Vapor pressure	2 hPa at 20 °C
Density	0.85 g/cm ³
Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))
---------------------------	---------------------------------------------------------

Viscosity

- Kinematic viscosity	22 – 27 cSt at 40 °C
- Dynamic viscosity	71 – 75 mPa s at 20 °C

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

	Explosive properties	none
	Oxidizing properties	none
9.2	Other information	there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains re-active substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	inhalation: vapor	11 mg/l/4h
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	inhalation: dust/mist	1.37 mg/l/4h
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylenedi-, ethoxylated(NLP)	1290049-56-7	oral	200 mg/kg

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Contains . May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Other information

Repeated exposure may cause skin dryness or cracking.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	64742-47-8	LL50	>1,000 mg/l	fish	24 h
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclic, <2% aromatics	64742-47-8	EL50	>1,000 mg/l	aquatic invertebrates	24 h
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	LC50	>0.43 mg/l	fish	96 h
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	EC50	0.43 mg/l	aquatic invertebrates	48 h
(Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8	ErC50	6.3 mg/l	algae	72 h
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylene-di-, ethoxylated(NLP)	1290049-56-7	LC50	0.13 mg/l	fish	96 h

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Amines, N-(C16-18 (even numbered) and C18-unsatd. alkyl) trimethylene-di-, ethoxylated(NLP)	1290049-56-7	EC50	0.31 mg/l	aquatic invertebrates	48 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number	not subject to transport regulations
14.2 UN proper shipping name	not assigned
14.3 Transport hazard class(es)	not assigned
14.4 Packing group	not assigned
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	There is no additional information.

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

VOC content

Regulated Volatile Organic Compounds (VOC-EPA): Regulated Volatile Organic Compounds (VOC-Cal ARB):

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
EU	REACH Reg.	all ingredients are listed or exempt from listing
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
 NDSL Non-domestic Substances List (NDSL)
 REACH Reg. REACH registered substances
 TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

Abbr.	Descriptions of used abbreviations
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STOT RE	Specific target organ toxicity - repeated exposure
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H227	Combustible liquid.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.

Interflon Fin Super Dry Lube

Version number: 1.7

Date of issue: 2019-10-24:

Code	Text
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.