

## Interflon Fin Gear Additive

### Additive for transmission oil

#### Product description

Improves transmission oil performance and reduces vibrations and noise well beyond the universal standards. Use whenever oil reaches its performance limit or does not meet the application requirements.

Contains MicPol® Technology to provide the optimum balance between thermal stability and wear protection for heavy-duty durability. Adds value by reducing oil temperature and friction while prolonging useful oil life.

#### Application

For the use in enclosed gear drives, final drives differentials, PTO's, and transmissions in cars, trucks, busses, and motorbikes; agricultural, marine and construction equipment, forklifts, lawn-mowers, power generators and many other types of vehicles and machines. Not suitable for transmissions with wet clutches.

Can be mixed with most mineral or synthetic transmission oils, except for polyglycol based lubricants. Not suitable for systems where filters with < 20 microns are used.

#### Advantages

- Smoother gear shifting
- Reduces vibrations, noise and oil temperature
- Reduces energy consumption
- Extends useful oil life
- Provides better seal protection

#### Instructions for use

Shake or stir before use according to the size of the packaging. Drain the old oil, change filters when present. Mix 4-6% of Interflon Fin Gear Additive with the new oil during each oil change. Refer to your Technical Advisor to ascertain compatibility.

Not suitable for use in automatic transmissions.

#### Safety regulations

See safety data sheet.

#### Packaging

See our current article list.

#### Transport regulations

See safety data sheet.

## Interflon Fin Gear Additive

### Additive for transmission oil

#### Technical data

Property	Result	Method
Composition	Mixture of mineral oils MicPol®.	
Colour	White	
Odour	Oily	
Density @ 20°C	0.89 g/cm <sup>3</sup>	
Dynamic viscosity @ 20°C	1400 mPas	ASTM D2983
Particle size MicPol®	0.05-15 µm	
Lowest application temperature	-20°C	
Highest application temperature	150°C	
Suitable for filters	>20 µm	
Shelf life*	4 years	

\* Shelf life of the product when stored at room temperature in the original and unopened packaging.

*Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice.*

---

**INTERFLON BV, P.O. Box 1070**  
**NL-4700 BB Roosendaal, The Netherlands**  
**Tel. + 31 (0) 165 55 39 11 / [www.interflon.com](http://www.interflon.com)**

---

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.

Interflon®/MicPol® is a registered trademark of Interflon BV.