

Interflon Metal Clean (aerosol)

Powerful cleaner and degreaser with high pressure spray

Product description

Cleans and degreases surfaces, machine parts and chains. Removes oil, grease, tar, resin, silicones, glue and other contaminants from surfaces, machine parts and chains. Has a mild smell, dries quickly and leaves no residue behind. Because of the spray pressure, difficult parts to reach can be cleaned quick and easy. Does not contain chlorinated solvents.

Listed by the NSF for use in the food industry as a degreaser, adhesive and glue remover (NSF A1) with registration number [140150](#).

Application

For cleaning and degreasing of bearings, gear wheels, locks, cylinders, chains, sliding, hinges, axles, spindles, conveyor belts, brake systems etc. Also especially suitable as a cleaner for asbestos free linings. Do not use for cleaning rubber, plastic components or safety glass.

Advantages

- Removes oil, grease and other contaminants
- Cleans, degreases and evaporates rapidly
- Does not contain chlorinated solvents
- Leaves no residue behind
- Powerful jet for parts which are difficult to reach
- Aerosol can be used in every position

Instructions for use

Spray liberally onto parts. Allow to penetrate and wipe with a clean cloth or paper. With severe soiling, repeat if necessary. For use in the food industry. All food products and packaging materials must be removed or covered before cleaning. After using, all surfaces must be washed with a detergent solution and rinsed with potable water.

It is advisable to test a small inconspicuous area to make sure that the cleaning agent does not adversely affect or damage the surface being cleaned. Do not apply to hot surfaces. When cleaning large vertical areas, apply the product from the bottom and work upwards ensuring that the whole area is covered. Cleaning away any dirt is best done from the top in a downwards direction to prevent leaving any streak marks. Do not use the product or allow to dry in direct sunlight.

Note: Interflon Metal Clean (aerosol) is a very strong cleaner which can affect elastomers and rubbers.

Safety regulations

See safety data sheet.

Packaging

See our current article list.

Transport regulations

See safety data sheet.

Interflon Metal Clean (aerosol)

Powerful cleaner and degreaser with high pressure spray

Technical data

Property	Result	Method
Composition	Mixture of solvents. Propellant carbon dioxide	
Colour	Colourless	
Odour	Citrus	
Density @ 20°C	0.77 g/cm ³	
Vapor pressure @ 20°C	162 hPa	
Evaporation speed	4.2 (n-BuAc = 1)	
Biodegradability	98%	OECD 302-B (modified)
Highest application temperature	40 °C	
Shelf life*	6 years	

*Shelf life of the product when stored at room temperature in the original and unopened packaging.

Typical properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice.

INTERFLON BV, P.O. Box 1070
NL-4700 BB Roosendaal, The Netherlands
Tel. + 31 (0) 165 55 39 11 / www.interflon.com

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should not therefore be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.

Interflon®/MicPol® is a registered trademark of Interflon BV.