

## MINERAL ATF OIL.

This is a mineral lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.



## APPLICATIONS

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

## PERFORMANCE LEVEL

- Dexron IID/IIIE/IIIF/IIIG/IIIH
- MB 236.1/236.5/236.6/236.7/236.9
- Ford Mercon/M2C138-CJ/166-H
- MAN 339 Typ Z1/V1
- Allison C4/TES-389
- Cat TO-2
- Voith 55.6335 (G607)
- Volvo 97341
- ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C

## FEATURES

Frictional properties : smooth shift performance.  
Anti-wear protection : extended transmission life.  
Extended oil life : excellent thermal and oxidation stability.

## CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.855
Viscosity 40 °C	mm <sup>2</sup> /s		33.9
Viscosity 100 °C	mm <sup>2</sup> /s		7.1
Viscosity Index			179
Flash Point COC	°C		196
Pour Point	°C		-45
Brookfield viscosity at -40 °C	mPas		17500
Color			RED

## PACKAGING

