

SYNTHETIC ATF OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.



APPLICATIONS

Mainly intended for the ZF-6 speed automatic transmissions, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid (e.g. Audi Quattro).

PERFORMANCE LEVEL

- AML: 4G4319A509/AA/S
- BENTLEY: PY112995PA
- BMW: 83220142516
- BMW: M-1375.4
- HYUNDAI: 040000C90SG
- JAGUAR: Fluid 8432
- LAND ROVER: TYK500050
- MASERATI: 231603
- VW: G 055 005
- ZF: TE-ML 11

FEATURES

Anti-wear protection : significantly extended transmission life.
 Frictional properties : very smooth gear shifting, no vibration.
 Extended oil life : excellent thermal and oxidation stability.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.845
Viscosity 40 °C	mm ² /s		31.0
Viscosity 100 °C	mm ² /s		6.2
Viscosity Index			153
Flash Point COC	°C		202
Pour Point	°C		-48
Brookfield viscosity at -40 °C	mPas		9500
Color			AMBER

PACKAGING

