

SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils, formulated to meet Euro 4 and Euro 5 norms and the demanding MB 229.51 specifications, and to ensure exceptional performance in terms of oxidation resistance, soot and sludge formation. It is a Mid SAPS oil of the latest generation with low sulfated ash, sulfur and phosphorus content. It provides complete protection of after-treatment devices and Diesel Particulate Filters.



APPLICATIONS

Euro 4 and 5 gasoline and diesel engines of Mercedes Benz, Smart and Chrysler vehicles that are equipped with a DPF. Fully backwards compatible for engines of previous generations (Euro 1, 2, 3).

PERFORMANCE LEVEL

- ACEA C3
- API SN
- BMW LONGLIFE-04
- MB 229.51
- MB 229.31
- VW 502 00
- VW 505 00
- VW 505 01

FEATURES

Total engine protection : Outstanding engine cleanliness and durability.
 After Treatment protection : Complete protection of the DPF filter.
 Fuel economy : Lower fuel consumption and CO2 emissions.

CHARACTERISTICS

	unit	method	average value
Density at 15 °C	kg/l		0.851
Viscosity -30 °C	mPas		5540
Viscosity 40 °C	mm ² /s		68.90
Viscosity 100 °C	mm ² /s		12.10
Viscosity Index			175
Flash Point COC	°C		228
Pour Point	°C		-39
Total Base Number	mgKOH/g		7.1

PACKAGING

