



Prestone



SAFETY DATA SHEET Simoniz High Build Primer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Simoniz High Build Primer
Product number	SIMB90D
REACH registration notes	This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Car maintenance product. Primer.
------------------------	----------------------------------

1.3. Details of the supplier of the safety data sheet

Supplier	A Holts Car Care Product Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com
Contact person	Contact Email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone	UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167
----------------------------	---

National emergency telephone number	http://echa.europa.eu/en/web/guest/support/helpdesks/national-helpdesks/list-of-national-helpdesks
--	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Eye Dam. 1 - H318 STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC)	Xi;R36. F+;R12. R52/53,R66,R67.
--	---------------------------------

2.2. Label elements

Simoniz High Build Primer

Pictogram



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated
 H318 Causes serious eye damage.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
 P101 If medical advice is needed, have product container or label at hand.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/ container in accordance with local regulations.

Contains

ACETONE, BUTYL ACETATE -norm, BUTANOL-norm, PROPAN-2-OL

Supplementary precautionary statements

P273 Avoid release to the environment.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/ doctor.
 P312 Call a POISON CENTER/ doctor if you feel unwell.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ACETONE	30-60%
CAS number: 67-64-1	EC number: 200-662-2
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 2 - H225	F;R11 Xi;R36 R66 R67
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
BUTANE	10-30%
CAS number: 106-97-8	EC number: 203-448-7
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Gas 1 - H220	F+;R12
Press. Gas	

Simoniz High Build Primer

BUTYL ACETATE -norm		10-30%
CAS number: 123-86-4		EC number: 204-658-1
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 R66 R67	
STOT SE 3 - H336		
ISOBUTANE		5-10%
CAS number: 75-28-5		EC number: 200-857-2
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Gas 1 - H220	F+;R12	
Press. Gas		
2-METHOXY-1-METHYLETHYL ACETATE		5-10%
CAS number: 108-65-6		EC number: 203-603-9
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xi;R36	
BUTANOL-norm		1-5%
CAS number: 71-36-3		EC number: 200-751-6
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xn;R22 Xi;R37/38,R41 R67	
Acute Tox. 4 - H302		
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
STOT SE 3 - H335, H336		
PROPAN-2-OL		1-5%
CAS number: 67-63-0		EC number: 200-661-7
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Xi;R36 R67	
Eye Irrit. 2 - H319		
STOT SE 3 - H336		
TRIZINC BIS(ORTHOPHOSPHATE)		1-5%
CAS number: 7779-90-0		EC number: 231-944-3
M factor (Acute) = 1	M factor (Chronic) = 1	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Aquatic Acute 1 - H400	N;R50/53	
Aquatic Chronic 1 - H410		

Simoniz High Build Primer

N-Ethyl-2-pyrrolidone	<1%
CAS number: 2687-91-4	EC number: 220-250-6
Classification	Classification (67/548/EEC or 1999/45/EC)
Eye Dam. 1 - H318	Repr. Cat. 1;R61. Xi;R41.
Repr. 1A - H360D	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Keep affected person away from heat, sparks and flames. Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Not relevant.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	If liquid has entered the eyes, proceed as follows. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Get medical attention promptly if symptoms occur after washing.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	Due to the physical nature of this material it is unlikely that swallowing will occur.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Risk of explosion if heated. Containers can burst violently or explode when heated, due to excessive pressure build-up.
-------------------------	---

5.3. Advice for firefighters

Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.
---	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	For personal protection, see Section 8.
-----------------------------	---

Simoniz High Build Primer

6.2. Environmental precautions

Environmental precautions Not considered to be a significant hazard due to the small quantities used.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m³(Sk)

BUTANOL-norm

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 154 mg/m³(Sk)

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

Simoniz High Build Primer

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Rubber (natural, latex). EN374

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Grey.
Odour	Acetone. Ketonic.
pH	Not relevant.
Flash point	<0°C CC (Closed cup).
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 4.8 Upper flammable/explosive limit: 9.5
Relative density	0.860 - 0.900 @ 20°C
Solubility(ies)	Soluble in water.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

Simoniz High Build Primer

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 12,469.97

Inhalation Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache. Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is soluble in water. The product hardens to a solid, immobile substance.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Simoniz High Build Primer

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ADN packing group	None
ICAO packing group	None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

Simoniz High Build Primer

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	EH40/2005 Workplace exposure limits.
EU legislation	Dangerous Substances Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	12/01/2017
Revision	2
Supersedes date	04/06/2015
SDS number	15032
Risk phrases in full	R10 Flammable. R11 Highly flammable. R12 Extremely flammable. R22 Harmful if swallowed. R36 Irritating to eyes. R37/38 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R61 May cause harm to the unborn child. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.

Simoniz High Build Primer

Hazard statements in full

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated
H302 Harmful if swallowed.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360D May damage the unborn child.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.